



## **Dahua 2MP Full-Folor Network PT Camera DH-SD2A200HB-GN-AW-PV-S2**

Model No: DH-SD2A200HB-GN-AW-PV-S2



### **Price:**

---

Rs. 21,200

### **Warranty:**

---

2 Years(s) manufacturer warranty.  
2 Year Manufacturer Warranty.

### **Delivery:**

---

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

## Specifications:

---

- :Type: 2MP PT Camera
- :Image Sensor: 1/2.8" CMOS
- :Effective Pixels: 1920 (H) × 1080 (V)
- :Night Vision: 30 m (98.42 ft) (IR)
- :Focal Length: 4.0 mm
- :Field of View: H: 86.8° V: 47.1° D: 102.2°
- :Pan / Tilt: Pan: 0° –345° Tilt: 0° –80
- Video & Audio:Video Compression: H.264B; Smart H.265+; H.264; H.265; MJPEG (Sub Stream); Smart H.264+/PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1
- Video & Audio:Frame Rate: Main stream: 1080p/1.3M/720p (1–25/30 fps) Sub stream: D1/CIF (1–25/30 fps)
- Video & Audio:Audio: Two-Way Talk
- :Built-In Mic & Speaker: Yes, Built-in Mic & Speaker
- Notice Management:Motion Detection: Yes
- Notice Management:Human Detection: Yes
- Notice Management:Abnormal Sound Alarm: Yes
- Network:Wi-Fi: Yes
- Network:Apps: iOS; Android
- Network:Onvif: CGI; SDK; ONVIF (Profile S&T); P2P
- :Auxiliary Interface: Micro SD card (512 GB); FTP
- :Power Supply: 12 VDC/1.5 A±10%
- :Power Consumption: Basic: 3.5 W Max.: 11 W (illuminator + PT + speaker + heating glass)
- :Working Environment: –30 °C to +55 °C (–22 °F to +131 °F)
- :Dimensions: 140.5 mm × 111.0 mm (5.53" × 4.45")
- :Weight: 0.5 kg (1.10 lb)
- :Certification: CE:EN55032/EN50130-4/EN IEC61000-3-3/EN IEC61000-3-2/EN55024/EN55035/EN62368-1 FCC:47 CFR FCC Part15, Subpart B, ANSI C63.4:2014

Date: 2025-04-04 02:25