



Dahua Cooper 1U 1HDD WizSense Digital Video Recorder (DH-XVR1B08H-I)

Model No: DH-XVR1B08H-I



Price:

Rs. 27,290

Warranty:

2 Years(s) manufacturer warranty.
2 Year Manufacturer Warranty.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- :Type: 8 Channels Penta-brid 5M-N/1080p Cooper 1U 1HDD WizSense Digital Video Recorder
- :Model: DH-XVR1B08H-I
- :Main Processor: Industrial-grade processor
- :Operating System: Embedded Linux
- :Operating Interface: Web; Local GUI
- :SMD Plus Info: 8-channel: Secondary filtering for human and motor vehicle , reducing false alarms caused by leaves, rain and lighting condition change
- Audio / Video:Analog Camera Input: 8 channels, BNC: adaptive access by default; HDCVI, AHD, TVI and CVBS access can be configured.
- Audio / Video:Camera Input: 1. CVI: 5 MP, 4 MP, 1080p@25/30 fps, 720p@50/60 fps, 720p@25/30 fps.,2. TVI: 5 MP, 4 MP, 1080p@25/30 fps, 720p@25/30 fps.,3. AHD: 5 MP, 4 MP, 1080p@25/30 fps, 720p@25/30 fps.,4. CVBS: PAL/NTSC
- Audio / Video:IP Camera Input: Up to 12 channels of IPC access, 4 IP channels by default + 8 channels (analog channels are converted to IP channels), incoming bandwidth: 64 Mbps, recording bandwidth: 64 Mbps and outgoing bandwidth: 64 Mbps, *After IP channels are added beyond the existing channels, the AI Function (SMD) will be disabled.
- Audio / Video:Encoding Capacity: Main Stream:All channel 5M-N@(1 fps–10 fps); 4M-N/1080p@(1 fps–15 fps); 1080N/ 720p/960H/D1/CIF@(1 fps–25/30 fps) ,Sub stream: D1/CIF (1 fps–15 fps)
- Audio / Video:Dual-Stream: Yes
- Audio / Video:Video Bit Rate: 32 kbps–6144 kbps
- Audio / Video:Audio Sampling: 8 kHz, 16 bit
- Audio / Video:Audio Bit Rate: 64 kbps
- Audio / Video:Video Output: 1 HDMI, 1 VGA, HDMI/VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
- Audio / Video:Multi-Screen Display: When IP extension mode not enabled: 1/4/8/9,When IP extension mode enabled: 1/4/8/9/16
- Audio / Video:Third-party Camera Access: ONVIF; Panasonic; Sony; Axis; Arecont; Samsung
- Compression Standard:Video Compression: AI Coding; H.265+; H.265; H.264+; H.264
- Compression Standard:Audio Compression: G.711a; G.711u; PCM
- Network:Network Protocol: HTTP; HTTPS; TCP/IP; IPv4/IPv6; Wi-Fi; 3G/4G; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P; UPnP; IP Filter;FTP; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.)
- Network:Mobile Phone Access: iOS; Android
- Network:Interoperability: ONVIF 21.06; CGI Conformant
- Network:Browser: Chrome, IE 9 or later ,Firefox
- Network:Network Mode: Single-address mode
- Recording Playback:Record Mode: General; motion detection; intelligent; alarm, POS
- Recording Playback:Recording Playback: 1/4/9
- Recording Playback:Backup Method: USB device and network
- Recording Playback:Playback Mode: Instant playback, general playback, event playback, tag playback

- Alarm:General Alarm: Motion detection, video loss, tampering
- Alarm:Anomaly Alarm: No disk, disk error, low space, offline, ip conflict, MAC conflict
- Ports:Audio Input: 1-channel RCA, 8-channel BNC (Coaxial Audio)
- Ports:Audio Output: 1-channel RCA
- Ports:Two-Way Talk: Yes (share the same audio input with the first channel)
- Ports:HDD Interface: 1 SATA port, up to 16 TB. The maximum HDD capacity varies with environment temperature.
- Ports:USB: 2
- Ports:HDMI: 1
- Ports:VGA: 1
- Ports:Network Port: 1
- General:Power Supply: 12 VDC, 1.5 A
- General:Power Consumption: <7 W (without HDD)
- General:Weight: 0.57 kg (1.26 lb)
- General:Dimensions: 198.3 mm × 203.4 mm × 41.5 mm, (7.81" × 8.01" × 1.63") (W × D × H)
- General:Operating Temperature: −10 °C to +55 °C (+14 °F to +131 °F)
- General:Installation: Desktop
- General:Certifications: FCC: Part 15 Subpart B, CE: CE-LVD: EN 60950-1/IEC 60950-1, CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024
- :Color: Black

Date: 2024-09-08 07:09