



John Deere Tractor With Rotavator JD-5045D-WRT

Model No: JD-5045D-WRT



Price:

Rs. 7,500,000

Warranty:

1 Years(s) manufacturer warranty.

1 Year Or 1000 Hours.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Type: Tractors
- Capacity / Power: 45HP
- Clutch Type: Dual Clutch
- Single / Tandem Pump: Tandem
- Engine - Engine Power (kW): kW (bhp) (At Rated Speed): 437.57 (44.6)
- Engine - PTO Bhp: kW (bhp) (At Rated Speed): 370.86 (37.8)
- Engine - Rated RPM: 2300
- Engine - Cooling System: Coolant Cooled, With Overflow Reservoir Tank
- Engine - Low Idle, RPM: 850 (-50/+ 25)
- Engine - High Idle, RPM: 2500 (-25+50)
- Engine - FIP: Mico Bosch Inline
- Engine - Muffler: Underhood
- Engine - Fuel Shut-Off: Manual, Lockable
- Engine - Air Cleaner: 15 cm (6") Dry
- Engine - Radiator: Core 48mm Al
- Engine - Water Separator: Applicable
- Transmission - Clutch Type: Collar Shift
- Transmission - No Of Speeds: 8F+ 4R
- Transmission - PTO: Standard 540 At 2200 ERPM/ 540E @ 1705RPM
- Transmission - Final Reduction: Inboard Planetary
- Transmission - Differential Lock: Standard
- Transmission - Brakes: Wet Disc Brakes
- Hitches - Three Point Linkage, Cat: Cat 2
- Hitches - Lift Capacity At Hitch Points (Kg-f): 1400
- Hitches - Sway Bar / Chain: Chain
- Wheels / Axle/Support - Rear Tyre Size: 14.9*28 (Normal)/14.9x28(HLD)
- Wheels / Axle/Support - Wheel Fixing Arrangement: M20 Stud
- Wheels / Axle/Support - Front Tyre Size: 8 x 18 (Normal) / 8x18 (HLD)
- Electricals - Battery: One , 12V, 88Ah
- Electricals - Alternator: 40 Amp
- Electricals - Starter: 12 V, 2.5 KW
- Electricals - Rear Work Lamp: Standard
- Electricals - Pin Connector: Standard
- Electricals - Head Lamp: 60/55 W H-4 bulb (LHT)
- Electricals - Park Lamp & Tail Lamp: 5W, 21/5W
- Electricals - Neutral Safety Switch: PTO Lever
- Electricals - Turn Signal Light: 21 W
- Seat: Make: Harita, Sliding, Normal Comfort, Standard Seat Belt
- Fuel / Fuel Tank: 60 L
- Capacities - Engine Sump (lit): 6.5
- Capacities - Transmission (lit): 37
- Capacities - Hydraulics (lit): Common To Transmission
- Capacities - Cooling System (lit): 9.5
- Overall Dimensions - Wheel base, mm: 1950

- Overall Dimensions - Front Wheel Track, mm: 1420
- Overall Dimensions - Rear Wheel Track, mm: 1420
- Overall Dimensions - Turning Radius (w/o Brakes): 3.2
- Overall Dimensions - Turning Radius (with Brakes): 3
- Overall Dimensions - Tractor Weight, Kg (Front): 787
- Overall Dimensions - Tractor Weight, Kg (Rear): 1188
- Overall Dimensions - Tractor Weight, Kg (Total): 1975
- Overall Dimensions - Ground Clearance (At Drop Box): 365mm

Date: 2024-09-08 07:05